



M-LED 111 GE

With the introduction of the in-house developed M-LED 111 module we are preparing some of our icons for the future. Luminaires from the halogen era will now also be available with LED. The new LED module is replacing the AR111 lamp and comes in white structure or black matt. The M-LED 111 module is applicable for following 'AR111' (GE) luminaires: Bolster recessed, Nomad, Multiple, Multiple trimless, Lotis, Haloscan and Thub metal. Also fits AR111 modules of SL149, Multiple(x), Freeway, 2FLAT2C and Traffic.

Art. Nr. 11298009

SPECIFICATIONS

Lamp	1x LED Array			
Gear / Transfo	LED gear not incl.			
Weight	0.75kg			
Min. Distance	0.1 m			
IP	IP20			
Glow Wire Test	960°			
CRI	90			
Power supply	350mA 31Vf	500mA 32Vf	700mA 34Vf	900mA 35Vf
Connected load	11W	16.25W	23.6W	31.2W
Lumen	939lm	1283lm	1659lm	1947lm
Efficacy	85lm/W	79lm/W	70lm/W	62lm/W
UGR	15	16	17	17

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+			NEUTRAL WHITE 4000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
black struc	11298002	11298102	11298202	11298302	11298402	11298502	11298602	11298702	11298802
white struc	11298009	11298109	11298209	11298309	11298409	11298509	11298609	11298709	11298809



Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.