design Alberto Meda / Paolo Rizzatto, 2002

Type: Wall/Ceiling

Lamps: D41/32.22 22W FSC T5 2GX13

D41B/32.22

D41/40.55

55W FSC T5 2Gx13 D41B/40.55

D41/40.55 D

D41/40.40E 40W FSC T5 2GX13 (no ENEC)

Product use: Indoor, Outdoor

Unbreakable, watertight polycarbonate Materials:

Colors: Structure in metallized, transparent, white

Front finishes in opaline, trasparent

Description: Sealed, ultra-light, slender, this fitting follows the circular

shape of fluorescent lamps. Its minimal depth allows it to be fitted to ceilings or walls while appearing built-in. Metallic and trasparent finishes allow different

modulations of light.

IP65 Certifications:

(D41/40.32 version requires functional earthing) Insulation class:

Compasso d'Oro ADI Milano 2004, selection Awards:

Reference code: D41/32.22 1D41PI220000 trasparent metallized

white D41B/32.22 trasparent metallized

1D41PI220000 1D41PI220019 1D41PI220002 1D41PI22B000 1D41PI22B019 1D41PI22B002 1D4100550000 1D4100550019 white D41/40.55 trasparent

metallized 1D4100550002 1D410055B000 white

D41B/40.55 trasparent 1D410055B019 metallized

1D410055B002 white D41/40.55 D 1D410055D000 1D410055D019 trasparent metallized

1D410055D002 white

D41/40.40E 1D410040E000 trasparent

1D410040E019 metallized 1D410040E002 white







